



# VIVE SUBMITTAL SHEET

PTAC Direct Sales, Inc.  
185 S. Kimball Ave., Suite 130  
Southlake, TX 76092  
877.454.7822 (T)

Job Name: \_\_\_\_\_ Location: \_\_\_\_\_ Date: \_\_\_\_\_

Purchaser: \_\_\_\_\_ Installer: \_\_\_\_\_

Submitted to: \_\_\_\_\_ For: ☐ RNC ☐ R&R ☐ Commercial

## MODEL TP-N-731WO

### Wireless Universal (Optimized for PTAC's)

Up to 1 Heat 1 Cool Conventional

Up to 2 Heat 1 Cool Heat Pump

Battery or Hardwire

Programmable with Occupancy Sensor



### This model features:

- 7 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Universal subbase
- Simple private label badge system
- Setpoint limits
- Electric or gas configurable
- Mounts on wall or junction box
- Auto-changeover
- 5 Year Warranty
- 5 minute compressor delay protection (selectable on or off)
- Separate heating and cooling swing (cycle rate) adjustments
- Battery or 24V power
- Room temperature calibration adjustments
- Easy wire color coded terminal blocks
- On-Board Occupancy Sensor

### Specifications:

Application	1 Heat 1 Cool Conventional, 2 Heat 1 Cool Heat Pump
Programmability	Programmable with Occupancy Sensor
System Switch	Cool - Off - Heat
Display Range	41°F to 95°F (5°C to 35°C)
Control Range	44°F to 90°F (7°C to 32°C)
Display Accuracy	+/- 1°F
Heat Swing	Adjustable from 0.2°F to 2.0°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Terminals	R, C, Y, W, O, B, GH, GL
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating Ambient	32°F to +105°F (0°C to +41°C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions	4.7"W x 4.4"H x 0.8"D (119mm W x 112mm H x 20mm D)
Warranty	5 year warranty