



CHASSIS SPECIFICATIONS

PZE Series with Electric Heat				
Model	PZE07K3SB-A	PZE09K3SB-A	PZE12K3SB-A	PZE15K5SB-A
PERFORMANCE DATA:				
Cooling Btu	7200/6800	9600/9400	12000/11800	14500/14300
Cooling Watts	600/565	815/800	1050/1035	1420/1400
Energy Efficient Ratio, EER	12.0	11.8/11.8	11.4/11.4	10.2/10.2
Heater Size (kW)	3.6	3.6	3.6	5.0
Moisture Removal (pints/hr.)	0.7	1.2	2.1	3.0
Sensible Heat Ratio	87%	82%	77%	72%
ELECTRICAL DATA:				
Voltage(1 PHASE, 60 Hz)	230/208	230/208	230/208	230/208
Volt Range	253-187	253-187	253-187	253-187
Current (Amps)	2.6/2.7	3.5/3.8	4.5/5.0	6.2/6.7
Power Factor	0.99	0.99	0.96	0.99
Compressor LRA	13.0	20.0	28.5	34.5
Compressor RLA	2.5	3.3	5.3	6.4
Outdoor Fan Motor, HP	0.07	0.07	0.07	0.09
AIRFLOW DATA:				
Indoor CFM, HIGH	335	400	470	470
Indoor CFM, LOW	250	250	360	360
Vent CFM	75	75	75	75
PHYSICAL DATA:				
Sleeve Dimensions (H x W x D)	16" x 42" x 13 ³ / ₄ " (all models)			
Dimensions with Front (H x W x D)	16" x 42" x 21" (all models)			
Cut Out Dimensions (H x W x D)	16 ¹ / ₄ " x 42 ¹ / ₄ " (all models)			
Net Weight (lbs.)	104	108	113	115
Shipping Weight (lbs.)	126	110	135	137
R-410A Charge (oz.)	29.98	32.10	30.69	34.22
Dimensions with Packaging (inches)	19" x 45" x 25" (all models)			

PZH Series Heat Pump				
Model	PZH07K3SB-A	PZH09K3SB-A	PZH12K3SB-A	PZH15K5SB-A
PERFORMANCE DATA:				
Cooling Btu	7200/6800	9600/9400	12000/11800	14500/14300
Cooling Watts	600/565	815/800	1050/1035	1420/1400
Energy Efficient Ratio, EER	12.0/12.0	11.8/11.8	11.4/11.4	10.2/10.2
Reverse Heating Btu	6400/6300	8500/8200	11000/10800	13600/13200
Heating Watts	530/520	710/685	930/920	1180/1150
COP	3.55/3.54	3.51/3.51	3.47/3.44	3.38/3.36
Moisture Removal (pints/hr.)	0.7	1.2	2.1	3.0
Sensible Heat Ratio	87%	82%	77%	72%
ELECTRICAL DATA:				
Voltage(1 PHASE, 60 Hz)	230/208	230/208	230/208	230/208
Volt Range	253-187	253-187	253-187	253-187
Current (Amps)	2.6/2.7	3.5/3.8	4.5/5.0	6.2/6.7
Reverse Heat. Amps	2.3/2.5	3.0/3.3	4.0/4.4	5.1/5.5
Power Factor	0.99	0.99	0.96	0.99
Compressor LRA	13.0	20.0	28.5	34.5
Compressor RLA	2.5	3.3	5.3	6.4
Outdoor Fan Motor, HP	0.07	0.07	0.07	0.09
AIRFLOW DATA:				
Indoor CFM, HIGH	335	400	470	470
Indoor CFM, LOW	250	250	360	360
Vent CFM	75	75	75	75
PHYSICAL DATA:				
Sleeve Dimensions (H x W x D)	16" x 42" x 13 ³ / ₄ " (all models)			
Dimensions with Front (H x W x D)	16" x 42" x 21" (all models)			
Cut Out Dimensions (H x W x D)	16 ¹ / ₄ " x 42 ¹ / ₄ " (all models)			
Net Weight (lbs.)	105	109	114	116
Shipping Weight (lbs.)	127	131	136	138
R-410A Charge (oz.)	29.98	32.10	30.69	34.22
Dimensions with Packaging (inches)	19" x 45" x 25" (all models)			

Operating range 0°-115°F.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

Receptacles and Fuse Types		
Voltage	230V	
Amps	20	30
Heater Size	3.6 kW	5.0 kW
Receptacles		
NEMA# Receptacle	6-20R	6-30R
NEMA# Plug	6-20P	6-30P



PTAC DIRECT SALES, INC.
185 S. KIMBALL AVE., SUITE 130
SOUTHLAKE, TX 76092
877.454.7822