



PTAC

2023 PRODUCT GUIDE

Expect comfort and reliability
from one of the toughest names in the industry.

Hotpoint® America's hardest working appliances.

PTAC Direct Sales, Inc.
185 S. Kimball Ave.,
Suite 130
Southlake, TX 76092
877.454.7822 (T)

DESIGNED FOR DEPENDABILITY

PROVIDING A BETTER ENVIRONMENT

2 Fan Speeds Plus Auto Mode

Give guests control over their comfort with two fan speeds plus auto mode to choose from.

4 Temperature-Limiting Options

Easily select one of four temperature ranges for peak efficiency and total customer comfort.

Dry Mode

Runs unit on low cool to allow for higher dehumidification levels in high humidity areas.

Intuitive Display

Allow guests to easily customize their preferred settings and reduce maintenance calls with an easy-to-use control panel.

Slinger Ring Condensate Removal

Reduces condensate volume and increases energy efficiency during cooling.

Automatic Emergency Heat

Keep guests comfortable with a heating option that automatically kicks in when temperatures drop and heat pumps shut down.

Freeze and Frost Protection

Automatic indoor frost control keeps units operating in peak condition.

Auto Power Recovery

In case of power failures, units automatically resume their operation when power restores, reducing maintenance calls.

Self-Diagnostics

Quickly and easily identify service needs with a nine-point diagnostic code system.

Constant Fan Button

Gives guests the option of running the indoor fan continuously even if the unit is in off mode.

GE APPLIANCES IS COMMITTED TO REDUCING OUR ENVIRONMENTAL IMPACT



Its increased efficiency over R410A means the air conditioner will use less refrigerant than previous models, thus improving its environmental impact over the life of the product.

Why R32?

R32 is easy to recycle and has a 30% lower GWP than R410A. Its proven track record in Europe has led GE Appliances to choose this refrigerant for their Hotpoint and GE Through-The-Wall Air Conditioners. Like R410A, R32 has a zero ozone depletion potential and is easy to charge and recover.





**ROOM
FRONT**

CHASSIS

**WALL
SLEEVE**
(Sold Separately)

**OUTDOOR
GRILLE**
(Sold Separately)





PROVIDE TOTAL COMFORT WITH COMPLETE CONFIDENCE

1-YEAR FULL PARTS & LABOR WARRANTY

Protected for 1 year after original date of purchase

Hotpoint® will provide—free of charge—all labor and related service costs to replace any part of the air conditioner which fails due to a defect in materials or workmanship.

2–5-YEAR LIMITED WARRANTY

Protected for 2–5 years after original date of purchase

Hotpoint will provide—free of charge—all labor and related service costs to replace any part of the Sealed Refrigerating System (the compressor, condenser, evaporator, connecting tubing and the makeup air system) which fails due to a defect in materials or workmanship.

5-YEAR LIMITED WARRANTY

Protected for 5 years after original date of purchase

Hotpoint will provide—free of charge—a replacement part for fan motors, switches, heater, heater protectors, compressor overload, solenoids, circuit boards, auxiliary controls, thermistors, freeze sentinel, frost controls, ICR pump, capacitors, varistors and indoor blower bearing, if this part fails due to a defect in materials or workmanship. Customers will be responsible for any labor and related service costs.

ADDITIONAL FEATURES

- ◆ 24 VAC Remote wall thermostat compatibility
- ◆ Tangential fan for smooth airflow and sound
- ◆ Factory attached power cord on all models*
- ◆ Heat pump models include staged heating
- ◆ Energy-efficient heat pump models available
- ◆ Removable filters for easy maintenance

*A sub-base (sold separately) and chaseway (included with unit) connects sub-base to junction box on unit and is required when installing 265V models. Failure to do so will NOT meet NEC code and compliance.

ACCESSORIES



◆ **Hotpoint 2 Fan Speeds Wall Thermostat**
RAK148H2A



◆ **Hotpoint Wall Thermostat**
RAK148H2



◆ **Hotpoint Wall Case**
RAB80



◆ **Hotpoint Grille**
RAG70



◆ **Hotpoint Filter**
RAA70



◆ **Curtain Guard**
RAK44

HOTPOINT PTAC NOMENCLATURE

AH

12

H

09

D

3

B

Brand
H=Hotpoint® PTAC

Unit Series
Chassis series

Unit Type
E= cooling with electric resistance heat
H= cooling/heat pump with backup electric heat

Nominal Cooling Capacity
07=7,000 BTUH cooling
09=9,000 BTUH cooling
12=12,000 BTUH cooling
15=15,000 BTUH cooling

Voltage/Phase/Frequency
D=230/208 volt, single phase, 60 Hz
E=265 volt, single phase, 60 Hz

Heater Watts/Amps
2=2.5 kW; 15 amp
3=3.5 kW; 20 amp
5=5.0 kW; 30 amp

Special Features
B=base unit

HOTPOINT COOL SERIES

	HOTPOINT 230/208V							
	COOLING WITH ELECTRIC RESISTANCE HEAT							
	AH12E07D2B	AH12E07D3B	AH12E09D2B	AH12E09D3B	AH12E12D3B	AH12E12D5B	AH12E15D3B	AH12E15D5B
Voltage	230/208	230/208	230/208	230/208	230/208	230/208	230/208	230/208
PERFORMANCE								
Cooling BTUH	7,400/7,300	7,400/7,300	9,200/9,000	9,200/9,000	12,000/11,800	12,000/11,800	14,500/14,300	14,500/14,300
EER (BTU/Watt)	13.1	13.1	11.3	11.3	10.7	10.7	10.3/10.4	10.3/10.4
Heating Watts	2,580/2,150	3,500/2,897	2,580/2,150	3,500/2,897	3,500/2,897	5,000/4,100	3,500/2,897	5,000/4,100
FEATURES								
Refrigerant Type	R32	R32	R32	R32	R32	R32	R32	R32
Electronic Controls	◆	◆	◆	◆	◆	◆	◆	◆
LCDI Power Cord	◆	◆	◆	◆	◆	◆	◆	◆
Remote Thermostat Capable	◆	◆	◆	◆	◆	◆	◆	◆
Slide-In Chassis	◆	◆	◆	◆	◆	◆	◆	◆
Discharge Grille	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position
Fan Motors	2	2	2	2	2	2	2	2
Fan Speeds (includes Auto Mode)	3	3	3	3	3	3	3	3
Heat - Cool	◆	◆	◆	◆	◆	◆	◆	◆
Rotary Compressor	◆	◆	◆	◆	◆	◆	◆	◆
Fan Cycle Control	◆	◆	◆	◆	◆	◆	◆	◆
Freeze Control	◆	◆	◆	◆	◆	◆	◆	◆
Automatic Indoor Frost Control	◆	◆	◆	◆	◆	◆	◆	◆
Auto Power Recovery	◆	◆	◆	◆	◆	◆	◆	◆
Central Desk Control Capable	◆	◆	◆	◆	◆	◆	◆	◆
Fresh Air Vent	Concealed Manual Vent Control / Vent Air Filter							
WEIGHT & DIMENSIONS								
Overall Dimensions (including room cover) (WxHxD in in.)	42 x 16 x 21							
Net Weight	102 lb	102 lb	98 lb	98 lb	109 lb	109 lb	113 lb	113 lb
Approximate Shipping Weight	112 lb	112 lb	109 lb	109 lb	120 lb	120 lb	123 lb	123 lb

HOTPOINT PTAC NOMENCLATURE

AH	12	H	09	D	3	B
Brand H=Hotpoint® PTAC	Unit Series Chassis series	Unit Type E= cooling with electric resistance heat H= cooling/heat pump with backup electric heat	Nominal Cooling Capacity 07=7,000 BTUH cooling 09=9,000 BTUH cooling 12=12,000 BTUH cooling 15=15,000 BTUH cooling	Voltage/Phase/Frequency D=230/208 volt, single phase, 60 Hz E=265 volt, single phase, 60 Hz	Heater Watts/Amps 2=2.5 kW; 15 amp 3=3.5 kW; 20 amp 5=5.0 kW; 30 amp	Special Features B=base unit

HOTPOINT HEAT PUMP SERIES

HOTPOINT HEAT PUMP SERIES	HOTPOINT 230/208V								HOTPOINT 265V	
	HEAT PUMP WITH ELECTRIC RESISTANCE HEAT BACKUP									
	AH12H07D2B	AH12H07D3B	AH12H09D2B	AH12H09D3B	AH12H12D3B	AH12H12D5B	AH12H15D3B	AH12H15D5B	AH12H09E3B	AH12H12E3B
Voltage	230/208	230/208	230/208	230/208	230/208	230/208	230/208	230/208	265	265
PERFORMANCE										
Cooling BTUH	7,300/7,200	7,300/7,200	9,500	9,500	12,000/11,800	12,000/11,800	14,800/14,600	14,800/14,600	9,000	12,000
EER (BTU/Watt)	12.9/13.0	12.9/13.0	11.4	11.4	10.5	10.5	10.6	10.6	11.3	10.5
Heating HP BTUH	6,200/6,000	6,200/6,000	8,400/8,200	8,400/8,200	10,800/10,500	10,800/10,500	13,400/13,100	13,400/13,100	8,000	10,800
COP	3.6	3.6	3.4	3.4	3.2	3.2	3.2	3.2	3.3	3.2
Heating Watts	2,580/2,150	3,500/2,897	2,580/2,150	3,500/2,897	3,500/2,897	5,000/4,100	3,500/2,897	5,000/4,100	3,500	3,500
FEATURES										
Refrigerant Type	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
Electronic Controls	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
LCDI Power Cord	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Remote Thermostat Capable	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Slide-In Chassis	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Discharge Grille	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position
Fan Motors	2	2	2	2	2	2	2	2	2	2
Fan Speeds (includes Auto Mode)	3	3	3	3	3	3	3	3	3	3
Heat - Cool	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Rotary Compressor	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Fan Cycle Control	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Freeze Control	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Automatic Indoor Frost Control	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Automatic Emergency Heat	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Auto Power Recovery	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Central Desk Control Capable	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Fresh Air Vent	Concealed Manual Vent Control / Vent Air Filter									
WEIGHT & DIMENSIONS										
Overall Dimensions (including room cover) (WxHxD in in.)	42 x 16 x 21									
Net Weight	105 lb	105 lb	103 lb	103 lb	116 lb	116 lb	117 lb	117 lb	102 lb	113 lb
Approximate Shipping Weight	116 lb	116 lb	113 lb	113 lb	125 lb	125 lb	127 lb	127 lb	112 lb	127 lb



AIR&WATER
SOLUTIONS

Appliance Park
Louisville, KY 40225
hotpoint.com

OTGEA4649879011

Hotpoint®

America's hardest working appliances.

PTAC Direct Sales, Inc.
185 S. Kimball Ave.,
Suite 130
Southlake, TX 76092
877.454.7822 (T)